

# 2D Horizontal Profiler - 400 kHz [logo] found or type unknown

## Up to 130 m horizontal profiling range; ideal for side-wall applications

The 2D Horizontal Profiler is the ideal tool for current measurements from a physical structure in, for example, port entrances. This ADCP provides the two horizontal flow components at multiple distances from the mounting and is commonly used in online applications where immediate access to current data is critical.

### Highlights

- [image not found] Up to 130 m horizontal profiling range
- [/] Ideal for wall-mounted applications
- [/] Corrosion-free housing

### Applications

- [/] Port entrances with challenging flow conditions
- [/] Flow measurements upstream and downstream of tidal turbines
- [/] Flow measurements from marine structures at draft depth

## Technical specifications

### [arrow] Water velocity measurements

Maximum profiling range	100-130 m
Cell size	1.0-8.0 m
Number of cells	Typical 20-40, max. 128
Velocity range	$\pm 10$ m/s horizontal, $\pm 5$ m/s along beam
Accuracy	$\pm 1\%$ of measured value $\pm 0.5$ cm/s
Velocity precision	Consult instrument software
Maximum output rate	1 Hz
Internal sampling rate	3 Hz

### [arrow] Echo intensity

Sampling	Same as velocity
Resolution	0.45 dB
Dynamic range	90 dB
Transducer acoustic frequency	400 kHz
Number of beams	2, slanted at 25°
Beam width	1.7°
Beam width vertical beam	N/A

### [arrow] Wave measurement option (AST)

Maximum depth	N/A
---------------	-----

[ arrow ]

### Wave measurement option (AST)

Data types	N/A
Sampling rate velocity (output)	N/A
Sampling rate AST (output)	N/A
No. of samples per burst	N/A

[ arrow ]

### Wave estimates

Range	N/A
Accuracy/resolution (Hs)	N/A
Accuracy/resolution (Dir)	N/A
Period range	N/A
Cut-off period (Hs)	N/A
Cut-off period (dir)	N/A

[ arrow ]

### Sensors

Temperature:	Thermistor embedded in housing
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C
Temp. time response	< 5 min
Compass:	Magnetoresistive
Accuracy/resolution	2°/0.1° for tilt <15°
Tilt:	Liquid level
Accuracy/resolution	0.2°/0.1°
Maximum tilt	30°
Up or Down	Automatic detect
Pressure:	Piezoresistive
Range	0-100 m
Accuracy	0.5% of full scale (optional 0.1% of full scale)
Resolution	0.005% of full scale

[ arrow ]

### Analog inputs

No. of channels	2
Supply voltage to analog output devices	Three options selectable through firmware commands: 1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA
Voltage input	0-5 V
Resolution	16-bit A/D

[ arrow ]

### Data recording

Capacity 9 MB, can add 4/16 GB  
Profile record Ncells\*9 + 120 bytes  
Wave record N/A  
Mode Stop when full (default) or wrap mode  
[ arrow ]

### Real-time clock

Accuracy ±1 min/year  
Backup in absence of power 1 year  
[ arrow ]

### Data communications

I/O RS-232 or RS-422. Software supports most commercially available USB-RS-232 converters  
Communication baud rate 300-115200 Bd  
Recorder download baud rate 600/1200 kBd for both RS-232 and RS-422  
User control Handled via "AWAC" software, or ActiveX®controls.  
Output formats NMEA, Binary. Prolog provides same types also for processed wave and current data  
[ arrow ]

### Connectors

Bulkhead MCBH-2-FS, MCBH-8-FS, optional Souriau M-series metal connector for online use  
Cable PMCIL-8-MP on 10 m polyurethane cable  
[ arrow ]

### Software

Functions Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)  
[ arrow ]

### Power

DC input 9-18 V DC  
Maximum peak current 3 A  
Avg. power consumption Typical 1 W when sampling  
Sleep current < 100 mA  
Transmit power 1-30 W, 3 adjustable levels  
[ arrow ]

### Environmental

Operating temperature -4 to +40 °C  
Storage temperature -20 to +60 °C  
Shock and vibration IEC 721-3-2  
EMC approval IEC 61000

[ arrow ]

### **Environmental**

Depth rating 300 m  
[ arrow ]

### **Materials**

Standard model POM and polyurethane plastics with titanium fasteners  
[ arrow ]

### **Dimensions**

Maximum diameter 306 mm

Maximum length 203 mm  
[ arrow ]

### **Weight**

Weight in air 8.8 kg

Weight in water 3.2 kg  
[ arrow ]

### **Online cable**

Polyurethane jacket, Shore D hardness, 13 mm in diameter, max 2 km. Inquire for longer cables