


# DVL1000 - 300 m found or type unknown

## Bottom-track from over 0.2 to 75 m range; 300 m max. operational depth

The DVL1000 is the world's smallest survey-grade Doppler Velocity Log. It combines compact design with unprecedented functionality, being able to fly higher in the water column and closer to the seabed than similar equipment. This version has a maximum operational depth of 300 m and is ideally suited for subsea navigation where size and weight are a concern. This 1 MHz Doppler Velocity Log is used by industry leaders in the subsea market because of its high accuracy and state-of-the-art technology.

### Highlights

-  Industry-wide acceptance
- [ / ] Bottom track from 0.2-75 m range
- [ / ] Quality estimates - per beam and ping

### Applications

- [ / ] Diver navigation systems
- [ / ] Hand-portable unmanned underwater vehicles (UUVs)
- [ / ] Shallow-water UUVs

## Technical specifications

### Bottom velocity

Single ping std @ 3 m/s 0.5 cm/s  
Long-term accuracy ±0.1% / ±0.1 cm/s  
Minimum altitude 0.2 m  
Maximum altitude 75 m  
Velocity resolution 0.01 mm/s  
Maximum ping rate 8 Hz max

### [ arrow ] Water tracking

Minimum accuracy 0.3% of measured value ± 0.3 cm/s  
Minimum range 2.0 m

### [ arrow ] Current profiling

Minimum accuracy 0.3% of measured value ± 0.3 cm/s  
Velocity resolution 0.1 cm/s  
Interval User-specified Nth ping  
Maximum range 30 m  
Blanking 0.1 m  
Cell size 0.2-2.0 m  
Max # cells 150

[ arrow ]

## Environmental

Operating temperature -4 to +40 °C  
Storage temperature -20 to +60 °C  
Vibration IEC60068-2-64  
EMC approval IEC/EN 61000-6-2, 61000-6-3

[ arrow ]

## Mechanical

Depth rating 300 m  
Weight 1.30 kg  
Weight in water 0.15 kg  
Height 158 mm  
Diameter ø114 mm

[ arrow ]

## Hardware

Frequency of operation 1 MHz  
Beam width 2.9°  
Configuration 4-beam Janus array convex transducer, 25° beam angle  
Internal memory 16 GB / 64 GB optional  
Frequency of operation 500 kHz  
Bandwidth 25% centered at transmit frequency

[ arrow ]

## Interfaces

Serial (either serial or ethernet) Configurable RS-232 or RS-422, 8-pin male  
Ethernet 10/100 Mbits Auto MDI-X. TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client / Auto IP address assignment. UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping. Multiple simultaneous data format transmission possible. Data formats Nortek proprietary  
Data formats Nortek proprietary w/ 1 ms time stamp accuracy, NMEA0183, Variants of PDx  
Trigger Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (ethernet or serial) External TTL or 485 lines: (configurable Rising/Falling/Edges)

[ arrow ]

## Sensors

Pressure 0.1% FS /precision better than 0.002% of full scale per sample  
Temperature -4° to +40 °C ± 0.1 °C

[ arrow ]

### **Power**

DC input	12-48 V
Maximum continuous current	1.5 A
Average power	1.3 W*

\* Power based on 1 Hz sampling and altitude with greatest transmit pulse.

[ arrow ]

### **Materials**

Standard models POM housing