

Signature VM Coastal - 1000|500|250 kHz copy

[logo] not found or type

The Signature VM package delivers vessel-mounted AD2CP capabilities based on present-day technology

The Signature VM Coastal safeguards data quality, opens up new and unprecedented opportunities to the scientific community, and offers operational convenience and reduced complexity.

The Signature VM Coastal package includes the Signature1000, 500 or 250, allowing for great versatility in both the vessel-mounted and bottom-mounted configurations. By using a state-of-the-art and user-friendly vessel-mounted package, measurement errors and initial installation time can be greatly reduced.

Signature VM Coastal - 1000|500|250 kHz copy

[logo]

Highlights

- [/] A coherent system that is quick and convenient to operate
- [/] Fifth echosounder beam for sediment measurements down to the bottom (1000/500)
- [/] Ethernet ADCP and GNSS hardware, offering tight network timing
- [/] Simultaneous current and depth information in one place (1000/500)
- [/] Outstanding bottom-track performance, even under challenging conditions
- [/] Straightforward data-acquisition and processing software

Applications

- [/] Coastal surveys, up to 200 m depth
- [/] Port and harbor mapping
- [/] Studies of tidal currents
- [/] Sediment transport studies
- [/] Large-scale mixing studies

Signature VM Coastal - 1000|500|250 kHz copy

[logo]

Technical specifications

[arrow] Water velocity measurements for Signature VM 1000 KHZ

Profiling range*	30 m
Cell size	0.2-2 m
Max no. cells	256
Min. blanking	0.1 m
Minimum accuracy	0.3% of the measured value \pm 0.3 cm/s
Velocity resolution	0.1 cm/s
Maximum sampling rate	14 Hz
No. of beams	4 slanted at 25 degrees

*) Maximum range depends on acoustic scattering conditions and transmit power.

[arrow] Bottom velocity measurements for Signature VM 1000 KHZ

Single ping std @ 3 m/s	0.5 cm/s
Long-term accuracy	\pm 0.1% / \pm 0.1 cm/s
Minimum altitude	0.2 m
Maximum altitude	30 m
Velocity resolution	0.01 mm/s
Maximum sampling rate	4 Hz

[arrow] Other

Temperature sensor range /accuracy	-4 °C to 40 °C / 0.1 °C
Pressure	Piezoresistive
Standard range	VM 1000/ VM 500: 0-100 m (inquire for options), VM 250: 0-300m (inquire for options)
Accuracy/precision	0.1% FS / better than 0.002% of full scale
Compass and tilt	Solid-state magnetometer
Data recording	16 GB (inquire for options)
Data cable	20 m Ethernet cable (inquire for options)
IO	Ethernet
DC Input	12-48 V DC

Signature VM Coastal - 1000|500|250 kHz copy

[logo]

[arrow] Environmental

Operating temperature	-4 °C to 40 °C
Storage temperature	-20 °C to 60 °C
Vibration	IEC 60068-1/IEC60068-2-64
EMC approval	IEC 61000
Depth rating	300 m – Bottom track is limited to surface vessels
Connectors	Straight fitted MCBH6F (Ethernet)
Housing	Small instrument housing
Material	POM with titanium fasteners and additional, reinforced transducer cups for VM 250

[arrow] Processing unit

Processor/memory	Intel i5/8 GB
Hard disk	SSD, 500 GB
Operating system	Windows® 10
Housing	Half 19" 2 HE case or 19" rack-mountable 1 HE
Dimensions	265x110x340 mm or 480x45x325 mm
Input	24 V DC, 20 W typical
Total weight	5.75 or 3.80 kg
Connections	Power, Signature ADCP, AN_GNSS, 2x HDMI, 2xLAN, 3x USB, 1x RS-232 (optional)

[arrow] Nortek Signature VM acquisition software

Acquisition	Signature VM - binary, GNSS compass - binary
Timing	< 0.6 s, IEEE1588/PTP for absolute timestamping (GNSS compass/Signature VM)
Configuration	Signature VM (partly)Advanced Navigation GNSS compass
Display	Vessel track in map, Bottom-track velocity, Bottom-track depth, Velocity magnitude and direction, Echo amplitude, Echo correlation, Vertical depth*, Vertical echogram; corrected relative volume backscatter (1000/500)*
Status	Signature VM + AN_GNSS compass
Output	Online: NMEA data formats and AD2CP format. Off-line CSV, ASCII VMT, MATLAB, MATLAB VMT, MATLAB QRev, KML

VESSEL-MOUNTED CURRENT PROFILER

Signature VM Coastal - 1000|500|250 kHz copy

[logo]

[arrow]

Nortek Signature VM acquisition software

*) Signature1000 and 500