

Signature55 [logo] found or type unknown

> 1000 m current profiling range for stand-alone and online applications

The Signature55 ADCP is a current profiler that combines an ultralong range with a compact layout. Novel ADCP transducer design allows 1000 m profiles concurrent with slightly shorter-range, finer resolution measurements using two different frequencies in the same instrument. The more than 90% lower power consumption (compared to similar ADCPs) also permits long-duration deployments operating on internal batteries only.

Highlights

- [image not found] > 1000 m current profiling range
- [/] Stand-alone and online applications
- [/] Concurrent high-resolution and long-range measurements

Applications

- [/] Observing deep-ocean current profiles
- [/] Current measurements for deep-water meteorological buoys
- [/] Fine and coarse deep-water current profiles

Technical specifications

[arrow] Water velocity measurements

Maximum profiling range*	1000 m (55 kHz), 600+ (75 kHz)
Cell size	5-20 m
Minimum blanking	2 m
Maximum number of cells	200
Velocity range (along beam)	User-selectable 1 or 5.0 m/s
Minimum accuracy	1% of measured value ± 0.5 cm/s
Velocity precision	Broadband processing, consult instrument software
Velocity resolution	0.1 cm/s
Max sampling rate	1 Hz (1/3 Hz at max power)

* Maximum range depends on transmit power and acoustic scattering conditions

[arrow] HR option (on 5th beam only)

Velocity range	N/A
Cell size	N/A
Profiling range	N/A
Range velocity limitations	N/A

[arrow] AD2CP measurement modes*

Single	Average
Concurrent	N/A
Alternate	Single (coarse/fine)

* US Patent 8223588
[arrow]

Echo intensity (along slanted beams)

Sampling	Same as velocity
Resolution/ dynamic range	0.5 dB / 70 dB
Transducer acoustic frequency	55 and 75 kHz
Number of beams	3, slanted at 20°
Beam width	4.5°-5.5°

[arrow]

Echo sounder option

Resolution	N/A
Number of bins	N/A
Transmit pulse length	N/A
Transmit pulse	N/A
Resolution / dynamic range	N/A

[arrow]

Wave measurement option

AST frequency	N/A
AST max distance	N/A
Maximum wave measurement depth	N/A
Height range	N/A
Accuracy/resolution (Hs)	N/A
Accuracy/resolution (Dir)	N/A
Period range	N/A
Cut-off period (Hs)	N/A
Cut-off period (dir)	N/A
Sampling rate (velocity and AST)	N/A

[arrow]

Ice

measurement option

Parameters	N/A
------------	-----

[arrow]

Sensors

Temperature:	Thermistor in head (sampled at meas. rate)
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C

[arrow]

Sensors

Temp. Time response	2 min
Compass:	Solid State magnetometer (max 1 Hz sample rate)
Accuracy/resolution	2° for tilt < 30°/0.01°
Tilt:	Solid State accelerometer (max 1 Hz sample rate)
Accuracy/resolution	0.2° for tilt < 30°/0.01°
Maximum tilt	Full 3D
Up or Down	Automatic detect
Pressure:	Piezoresistive (sampled at meas. rate)
Standard range	0-1500 m (inquire for options)
Accuracy/precision	0.1% FS / Better than 0.002% of full scale

[arrow]

AHRS option

Accelerometer dynamic range	± 2 g
Gyro dynamic range	± 250°/sec
Magnetometer dynamic range	± 1.3 Gauss
Pitch and roll range / resolution	± 90° (pitch) ± 180° (roll) /0.01°
Pitch and roll accuracy	± 2° (dynamic)*, ± 0.5° (static, ±30°)
Heading range / resolution	360°, all axis /0.01°
Heading accuracy	± 3° (dynamic)*, ± 2° (static, tilt < 20°)
Sampling rate	Same as measurement rate (up to 1 Hz)

* Dynamic specifications depends on the type of motion

[arrow]

Data recording

Capacity 16 GB, 64 GB or 128 GB (inquire for larger capacity)

Data record Consult instrument software

Mode Stop when full

[arrow]

Real-time clock

Accuracy ± 1 min/year

Clock retention in absence of external power 1 year. Rechargeable backup battery.

[arrow]

Data communications

Ethernet 10/100 Mbits Auto MDI-X, TCP/IP, UDP/IP, HTTP protocols, Fixed IP / DHCP client /Auto IP address assignment, UPnP and Nortek proprietary instrument discovery over Ethernet

Serial Configurable RS-232/RS-422 300-1250000 bps

[arrow]

Data communications

Recorder download
baud rate 20 Mbit/s (Ethernet only) - 1 GB in 6 minutes

Controller interface ASCII command interface over Telnet and serial
[arrow]

Connectors

Depending on
configuration MCBH6F (Ethernet), MCBH8F (serial), MCBH2F-G2 (pwr), optional
Souriau M-series metal connector for online use (14M)
[arrow]

Software

Functions Deployment planning, instrument configuration, data retrieval and conversion
(for Windows®)
[arrow]

Power

DC input 15-48 V DC

Maximum peak current 1.5 A

Max. average consumption at 1 Hz 15 W

Typical average consumption* 2 W

Sleep consumption 100 mA, power depending on supply voltage

Transmit power per beam 4-250 W, adjustable levels

Ping sequence Multiplexing or parallel

* 10 min. avg. profile, 1 cm/sec hor. Prec., Max cell size, max power, long range mode. Consult
SW for other configurations
[arrow]

Batteries

Internal One or two 540 Wh alkaline or 1800 Wh lithium

Duration Depending on configuration, consult software
[arrow]

Environmental

Operating temperature -4 to +40 °C

Storage temperature -20 to +60 °C

Vibration IEC60068-2-64

EMC approval IEC/EN 61000-6-2, 61000-6-3

Depth rating 1500 m
[arrow]

Materials

Standard model POM with titanium fasteners. Reinforced polyurethane transducer cups
[arrow]

Dimensions

Maximum diameter 648 mm
Maximum length with room for internal batteries 547 mm (1 battery), 747 mm (2 batteries)
Maximum length without room for internal batteries 314 mm
[arrow]

Weight

In air, no battery 65.5 kg
In water, no battery 25.1 kg
Battery 10.0 kg (2 x 540 Wh), 5.8 kg (2 x 1800 Wh)