

Aquadopp 3000 m



Single-point current meter designed for very long-term deployments

With all the features and capabilities of the standard Aquadopp, the deepwater Aquadopp 3000 m current meter has been used and proven by oceanographers around the world for almost 20 years. Thanks to innovative data diagnostic features for challenging environments, it provides exceptionally high-quality 3D currents in a form factor that is easy to install in any type of mooring line configuration, or simply attached to a bottom or surface platform.

Raw magnetometer data can be stored for post calibration of compass when used without the inductive modem option.



Aquadopp 3000 m

Highlights

- ✓ Single-point current meter
- ✓ Designed for very long-term deployments
- ✓ Diagnostics mode for mooring performance evaluation

Applications

- ✓ Studies of deep-water currents
- ✓ Studies of tidal currents
- ✓ Attached to mooring lines
- ✓ In conjunction with riser monitoring systems
- ✓ Measurements of unaffected currents from physical structures
- ✓ Alternative to conventional current meters with errors due to fouling
- ✓ Combination of currents and high-accuracy CTD data
- ✓ Near-bed current measurements from landers
- ✓ Deep ocean mining support

Aquadopp 3000 m

Technical specifications

→ Water velocity measurements

Maximum profiling range	N/A
Cell size	0.75 m
Minimum blanking	0.50 m
Maximum number of cells	1
Measurement cell position	0.5-5.0 m (user-selectable)
Default position (along beam)	0.50-2.0 m
Velocity range	±5 m/s
Accuracy	±1% of measured value ±0.5 cm/s
Velocity precision	Consult instrument software
Maximum sampling rate (output)	1 Hz
Internal sampling rate	23 Hz

→ Echo intensity

Sampling	Same as velocity
Resolution	0.45 dB
Dynamic range	90 dB
Transducer acoustic frequency	2 MHz
Number of beams	3
Beam width	3.4°

→ HR option

Maximum profiling range	N/A
Cell size	N/A
Minimum blanking	N/A
Maximum number of cells	N/A
Range/Velocity limitations	N/A
Accuracy	N/A
Max. sampling rate	N/A

→ Z-Cell option

Aquadopp 3000 m

Cell zero acoustic frequency	N/A
------------------------------	-----

Maximum profiling range	N/A
-------------------------	-----

Number of beams	N/A
-----------------	-----

→ Sensors

Temperature:	Thermistor embedded in head
--------------	-----------------------------

Temp. range	-4 to +40 °C
-------------	--------------

Temp. accuracy/resolution	0.1 °C/0.01 °C
---------------------------	----------------

Temp. time response	10 min
---------------------	--------

Compass:	Magnetometer
----------	--------------

Accuracy/resolution	2°/0.1° for tilt < 20°
---------------------	------------------------

Tilt:	Liquid level
-------	--------------

Accuracy/resolution	0.2°/0.1°
---------------------	-----------

Maximum tilt	30°
--------------	-----

Up or Down	Automatic detect
------------	------------------

Pressure:	Piezoresistive
-----------	----------------

Range	3000 m
-------	--------

Accuracy/precision	0.5% FS / 0.005% of full scale
--------------------	--------------------------------

→ Analog inputs

No. of channels	2
-----------------	---

Supply voltage to analog output devices	Three options selectable through firmware commands: 1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA
---	--

Voltage input	0-5 V
---------------	-------

Resolution	16-bit A/D
------------	------------

→ Data recording

Capacity	9 MB, can add 4/16 GB
----------	-----------------------

Data record	40 bytes
-------------	----------

Diagnostics record	40 bytes
--------------------	----------

Wave record	N/A
-------------	-----

Mode	Stop when full (default) or wrap mode
------	---------------------------------------

→ Real-time clock

Accuracy	±1 min/year
----------	-------------

Aquadopp 3000 m

→ Real-time clock

Backup in absence of power	4 weeks
----------------------------	---------

→ Data communications

I/O	RS-232 or RS-422
-----	------------------

Communication baud rate	300-115200 Bd
-------------------------	---------------

Recorder download baud rate	600/1200 kBd for both RS-232 and RS-422
-----------------------------	---

User control	Handled via "Aquadopp" software, ActiveX® function calls, or direct commands with binary or ASCII data output
--------------	---

→ Connectors

Bulkhead	MCBH-8-FS
----------	-----------

Cable	PMCIL-8-MP on 10 m polyurethane cable
-------	---------------------------------------

→ Software

Functions	Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)
-----------	---

→ Power

DC input	9-15 V DC
----------	-----------

Maximum peak current	3 A
----------------------	-----

Avg. power consumption	0.015 W
------------------------	---------

Sleep current	< 100 µA
---------------	----------

Transmit power	20 W
----------------	------

→ Batteries

Battery capacity	50 Wh (alkaline or Li-ion), 165 Wh (lithium), Single or dual
------------------	--

New battery voltage	13.5 V DC (alkaline)
---------------------	----------------------

→ Environmental

Operating temperature	-5 to +40 °C
-----------------------	--------------

Storage temperature	-20 to +60 °C
---------------------	---------------

Shock and vibration	IEC 721-3-2
---------------------	-------------

EMC approval	IEC 61000
--------------	-----------

Depth rating	3000 m
--------------	--------

→ Materials

Standard model	POM housing
----------------	-------------



Aquadopp 3000 m

→ Dimensions

Maximum diameter	84 mm
Maximum length	~500 mm (single battery) or +110 mm (double battery) depending on head configuration

→ Weight

Weight in air	3.6 kg
Weight in water	1.2 kg

→ Options

1) Alkaline, lithium or Li-ion external batteries, 2) Inquire for different head configurations