

## Aquadopp 6000 m -Legacy



This version of the Aquadopp is no longer available.

Please see the **Aquadopp Generation 2**.

This version of the Aquadopp remains functional and supported. Please visit our <u>support center</u> if you require assistance.

**Highlights** 

**Applications** 

## **Technical specifications**

Water velocity measurements	
Maximum profiling range	N/A
Cell size	0.75 m
Minimum blanking	0.50 m
Maximum number of cells	1
Measurement cell position	0.5-5.0 m (user-selectable)
Default position (along beam)	0.50-2.0 m
Velocity range	±5 m/s
Accuracy	$\pm 1\%$ of measured value $\pm 0.5$ cm/s
Velocity precision	Consult instrument software
Maximum sampling rate(output)	1 Hz
Internal sampling rate	23 Hz

Echo intensity	
Sampling	Same as velocity
Resolution	0.45 dB
Dynamic range	90 dB
Transducer acoustic frequency	2 MHz
Number of beams	3
Beam width	3.4°

Sensors	
Temperature:	Thermistor embedded in head

Date: 12/03/2025 nortekgroup.com

Sensors	
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C
Temp. time response	10 min
Compass:	Magnetometer
Accuracy/resolution	2°/0.1° for tilt < 20°
Tilt:	Liquid level
Accuracy/resolution	0.2°/0.1°
Maximum tilt	30°
Up or Down	Automatic detect
Pressure:	Piezoresistive
Range	6000 m
Accuracy/precision	0.5% FS / 0.005% of full scale
Analog inputs	
No. of channels	2
Supply voltage to analog output devices	Three options selectable through firmwarecommands: 1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA
Voltage input	0-5 V
Resolution	16 bit A/D
Data recording	
Capacity	9 MB, can add 4/16 GB
Data record	40 bytes
Diagnostics record	40 bytes
Wave record	N/A
Mode	Stop when full (default) or wrap mode
Real-time clock	
Accuracy	±1 min/year
Backup in absence of power	4 weeks
Data communications	
I/O	RS-232 or RS-422
Communication baud rate	300-115200 Bd
Recorder download baud rate	600/1200 kBd for both RS-232 and RS-422
User control	Handled via "Aquadopp" software, ActiveX $\$$ function calls, or direct commands with binaryor ASCII data output
Software	
Functions	Deployment planning, instrument configuration, data retrieval and conversion (for Windows®)
Power	
DC input	9-15 V DC
Maximum peak current	3 A
Avg. power consumption	0.015 W
Sleep current	< 100 μΑ
	·

Date: 12/03/2025 nortekgroup.com

Power	
Transmit power	20 W
Batteries	
Battery capacity	50 Wh (alkaline or Li-ion), 165 Wh (lithium), Single or dual
New battery voltage	13.5 V DC (alkaline)
Environmental	
Operating temperature	-5 to +40 °C
Storage temperature	-20 to +60 °C
Shock and vibration	IEC 721-3-4
EMC approval	IEC 61000
Depth rating	6000 m
Connectors	
Bulkhead	MCBH-8-FS titanium
Cable	PMCIL-8-MP on 10 m polyurethane cable
Materials	
Standard model	Titanium and POM
Dimensions	
Maximum diameter	84 mm
Maximum length	$\sim$ 500 mm (single battery), +110 mm (double battery) depending on head configuration
Weight	
Weight in air	7.6 kg
Weight in water	4.8 kg

Date: 12/03/2025 nortekgroup.com