

# **DVL 500 Compact**

6000 m. Generation 3

Bottom-track from 0.1 to 175 m range; 6000 m operational depth



The DVL 500 Compact combines the compact design of the standard DVL 1000 with the superior bottom-track range of the DVL 500. It can fly higher in the water column and closer to the seabed than similar equipment, enabling small vehicles to do bigger jobs.

Download our guide to Nortek DVLs here.

#### **Highlights**

- ✓ Bottom-track from 0.1-175 m range
- ✓ Per-ping and per-beam data quality estimates
- ✓ 6000 m operational depth

### **Applications**

- ✓ Next-generation compact survey vehicles
- Small vehicles requiring longer bottom track range in deep water
- ✓ Compact AUVs with high accuracy requirements
- ✓ Increase range of vehicles with existing DVL 1000 without vehicle redesign

# **Technical specifications**

Bottom velocity	
Single ping std @ 1.5 m/s	0.8 cm/s at 1/2 max altitude
Long-term accuracy	$\pm 0.1\%$ / $\pm 0.1$ cm/s (export-controlled), >1% (license-free)
Minimum altitude	0.1 m
Maximum altitude	175 m
Velocity resolution	0.01 mm/s
Maximum ping rate	8 Hz max

Water tracking	
Minimum accuracy	$0.3\%$ of measured value $\pm~0.3$ cm/s
Minimum range	4.0 m

Current profiling	
Minimum accuracy	$0.3\%$ of measured value $\pm~0.3$ cm/s
Velocity resolution	0.1 cm/s
Interval	User-specified Nth ping

Date: 12/03/2025 nortekgroup.com

Current profiling	
Maximum range*	70 m
Blanking	0.5 m
Cell size	0.5-4.0 m
Max # cells	140

*Dependent	on	measurement	conditions
------------	----	-------------	------------

Environmental	
Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60 °C
Vibration	IEC60068-2-64
EMC approval	IEC/EN 61000-6-2, 61000-6-3

Mechanical	
Depth rating	6000 m *
Weight	4.15 kg / OEM 2.5 kg
Weight in water	1.7 kg
Height	185 mm
Diameter	ø 114 mm

<sup>\*</sup> DVL 500c products delivered before March 2024 are depth rated to 4000m not 6000m. Please contact Nortek if you are unsure about the depth-rating of your instrument.

Hardware	
Frequency of operation	500 kHz
Beam width	5.8°
Configuration	4-beam Janus array convex transducer, 25° beam angle
Internal memory	16 GB / 64 GB optional
Frequency of operation	500 kHz
Bandwidth	25% centered at transmit frequency

Interfaces		
Serial (either serial or Ethernet)	Configurable RS-232 or RS-422, SubConn connector, 8-pin male	
Ethernet	10/100 Mbits Auto MDI-X. TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client /Auto IP address assignment. UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping. Multiple simultaneous data format transmission possible.	
Data formats	Nortek proprietary w/ 1 ms time stamp accuracy, NMEA0183, variants of PDx	
Trigger	Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (Ethernet or serial) External TTL or 485 lines: (configurable Rising/Falling/Edges)	

Sensors	
Pressure	0.1% FS /precision better than 0.002% of full scale per sample
Temperature	-4° to +40 °C ± 0.1 °C

## Power

Date: 12/03/2025 nortekgroup.com

DC input	12-48 V
Maximum continuous current	1.5 A
Average power	3.0 W*

<sup>\*</sup> Power based on 1 Hz sampling and altitude with greatest transmit pulse.

## **Materials**

Standard models

POM and titanium housing

Date: 12/03/2025 nortekgroup.com